GAST AD 220

Page 1 of 6 19 September 2013 Supercedes none MSDS #: MSOL447

# **Safety Data Sheet**

# SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

OLYMPIC OIL, LTD.

5000 W. 41st St., Cicero, IL 60804

Phone: 708-876-7900

Monday - Friday 6:00 A.M. - 4:30 P.M.

**Product Name** 

PRIMAR PNEUMATIC SAE 10 OIL

**SDS Number** 

MSOL447

**Transportation Emergency Phone** 

CHEMTREC 1-800-424-9300 (USA); +1 703-527-3887(Outside USA)

# **SECTION 2: HAZARDS IDENTIFICATION**

Appearance

Amber colored liquid

Odor

Mild

Principal Hazards

May cause mild, transient irritation to the eves

Prolonged or repeated exposure may cause mild irritation to the skin

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	WT % (approx)
Lubricating oil, petroleum	Mixture	90 – 99
Zinc Dialkyl Dithiophosphate	68649-42-3	0.1 - 0.9

#### SECTION 4: FIRST AID MEASURES

Eyes Immediately flush eyes with clean, low-pressure water for at least 15 minutes,

occasionally lifting the eyelids. Get medical attention if irritation develops or

persists.

Skin Wash skin thoroughly with plenty of soap and water. Immediately remove

contaminated clothing. Launder contaminated clothing before reuse. Discard saturated leather gloves and shoes. If irritation persists, get medical attention.

Oral DO NOT INDUCE VOMITING. If more than a half-cup full of this material is

swallowed, give quantities of water and obtain medical attention. Do not give anything by mouth to an unconscious person. If vomiting occurs, lower head

below knees to avoid aspiration.

Inhalation Vaporization is not expected at ambient temperatures. This material is not

expected to be an inhalation problem under the anticipated conditions of use. In

case of overexposure, move person to fresh air. If not breathing, administer

artificial respiration and oxygen.

Note to physician

Treat symptomatically.

#### **SECTION 5: FIRE FIGHTING MEASURES**

Flash Point

338°F. (>170°C)

Method of determination: COC D92

Extinguishing Media

Carbon dioxide, dry chemical, foam or water spray. Water may be effective, but may cause frothing and spattering. Cool tanks and exposed containers with

water. Material will float on water.

Fire Fighting Instructions For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of combustion products and oxygen deficiencies. If firefighters cannot work upwind to the fire, respiratory protective equipment must be worn.

Unusual Fire & Explosion Hazards

See Section 10 for additional information.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Ensure your own health and safety before attempting spill control or clean up. Take the proper precautions see Section 1 for Emergency Overview, Section 8 for Personal Protection and Section 13 for Disposal Considerations.

Small Spill

Remove all sources of ignition. Provide adequate ventilation during clean up. Personal protective equipment must be worn (see Person Protection section for recommendations). Absorb spill with an inert material (e.g., dry sand or earth), then place in a chemical waste container. Use caution, material may present a slipping hazard.

Large Spill

Contain spill and prevent it from entering all water bodies, if possible. Safely stop flow of spill. Evacuate non-essential personnel from immediate spill area. Ventilate area if spilled in a confined space or other poorly ventilated areas. In natural environments, get advice from ecologists on clean-up procedures. This material will float on water. Absorbent materials and pads can be used. Maximize product recovery for reuse or recycling. Transfer liquids and solid diking material to separate, suitable containers for recovery or disposal. Comply with all applicable laws. Spills may need to be reported to the National Response Center (800-424-8802).

#### **SECTION 7: HANDLING AND STORAGE**

Handling

Keep away from heat, sparks and flame. Keep containers closed when not in use. Use appropriate containment to avoid environmental contamination. Ground all handling equipment to prevent sparking. Avoid breathing vapors or mist. Avoid contact with eyes. Avoid prolonged exposure to skin. Hands should be washed thoroughly after handling.

Storage

KEEP OUT OF REACH OF CHILDREN! Odorous and toxic fumes may form

from decomposition of this material if stored in temperatures in excess of 113 Deg. F. (45 Deg. C.) for extended periods of time. Keep tightly closed in a dry,

cool, well ventilated place.

**Storage Temperature** 

Ambient

Storage Pressure

Atmospheric

# SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

#### **Exposure Guidelines:**

COMPONENT	OSHA		ACGIH	
	TWA	STEL	TWA	STEL
Oil mist, mineral	5 mg/m <sup>3</sup>	N/E	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Zinc Dialkyl Dithiophosphate	N/E	N/E	N/E	N/E

Engineering

Use adequate ventilation to keep oil mists of this material below applicable

Controls

guideline(s)/standard(s).

Respiratory Protection

Under normal conditions, a respirator is not required. If exposure exceeds the

occupational exposure limits, follow OSHA standards or equivalent and wear

proper NIOSH/MSHA-approved respiratory equipment.

Skin

Use chemical resistant gloves to avoid prolonged or repeated skin contact.

Protection Gloves should be replaced if signs of degradation or chemical breakthrough

occur. Do not wear rings, watches, or similar apparel that could trap material and cause a skin reaction. Long sleeve shirt is recommended. When leaving work

area, wash hands/exposed skin with soap and water.

Eye

Use splash goggles or face shield. Eye wash water should be available. Hard

Protection

contact lenses should not be worn.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (TYPICAL)

Appearance:

Amber

Flash Point:

338 Deg. F (>170 Deg. C) by COC D92

Odor:

Mild

**Specific Gravity:** 

0.86 - 0.88 at 60 Deg. F.

Solubility in Water:

Negligible

Pour Point:

Not Determined Not Determined

Vapor Pressure:

Not Determined

Vapor Density: Percent Volatile:

Negligible

Viscosity@ 100 Deg. C:

4.5 - 7.5 centistokes

#### **SECTION 10: STABILITY AND REACTIVITY**

Stability

Material is considered stable at room temperature and pressure. Avoid heat,

sparks and open flame.

Incompatibility

Strong oxidizing agents

Thermal

Decomposition

Smoke, carbon monoxide, carbon dioxide, aldehydes, and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may

also be released. Complete combustion will form oxides of the following

elements: nitrogen, sulfur, phosphorus and zinc.

**Polymerization** Conditions to

None None

avoid

# SECTION 11: TOXICOLOGICAL INFORMATION

Eye Irritation Mild, transient irritation may occur upon short-term exposure, based on

component data.

Not expected to be a primary irritant. Mild skin irritation may occur upon short-Skin Irritation

> term exposure, based on component data. Long-term exposure may cause redness, edema, drying and cracking of skin. Persons with pre-existing skin

conditions should avoid contact with this material.

Respiratory

Irritation

No significant adverse health effects are expected to occur under normal

conditions of use. However, exposure to petroleum mist at high levels may be

irritating to the nose, throat and lungs.

**Oral Toxicity** 

No significant adverse health effects are expected to occur upon short-term

exposure based on data from components.

**Dermal Sensitivity** 

This material contains an ingredient which is known to be sensitizer in animals,

and therefore prolonged or repeated skin contact with this material may cause an

allergic skin reaction.

**Chronic Toxicity** 

Carcinogenicity

No Data

This product is formulated with mineral oils, which are considered to be severely

refined and not considered to be carcinogenic under IARC. The IP346 test has

not been used to evaluate these oils.

Mutagenicity

**Teratogenicity** 

No Data

Reproductive

Toxicity

No Data

No Data

#### **SECTION 12: ECOLOGICAL INFORMATION**

This material is not expected to be readily biodegradable based on component Ecotoxicity

**Environmental** 

Component data indicates that plants and animals may experience harmful or fatal

Fate

effects when coated with petroleum products.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

To determine the proper method of disposal, refer to RCRA (40 CFR 261) as well as federal EPA and state and local regulations. Conditions of use may cause this material to become a "Hazardous Waste", as defined by state or federal laws. Use approved treatment, transporters and disposal sites in compliance with all applicable laws.

**EMPTY CONTAINER WARNING:** Empty containers contain residue, which may exhibit the hazards of the product. Do not attempt to refill or clean containers since residue is difficult to remove. Use proper bonding and grounding procedures.

#### **SECTION 14: TRANSPORT INFORMATION**

**DOT Hazard Class:** 

Not Regulated

UN/NAID No.:

None

ICAO/IATA:

IMDG:

Not Regulated Not Regulated

SECTION 15: REGULATORY INFORMATION

# GLOBAL REGULATORY INFORMATION

INVENTORY STATUS

United States (TSCA) All ingredients are on the inventory.

Other TSCA None known

Canada (DSL) All ingredients are on the inventory.

European Union (EINECS)

Japan (METI)

Philippines (PICCS)

South Korea (KECL)

Australia (AICS)

Contains an ingredient that may not be on the inventory. Contains an ingredient that may not be on the inventory. Contains an ingredient that may not be on the inventory. Contains an ingredient that may not be on the inventory.

China (IECSC) Contains an ingredient that may not be on the inventory.

# U. S. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 (SARA), Title III: This product contains less than 1% zinc

**SARA Extremely Hazardous list:** This product does not contain greater than 1.0% of any chemical on the SARA Extremely Hazardous List.

# SARA 311/312

Immediate (Acute) Health Effects	Yes
Delayed (Chronic) Health Effects	No
Fire Hazards	No
Reactivity Hazards	No

#### CERCLA Hazardous Substance: None known

Cal. Prop. 65

Based on information currently available, this product does not contain any chemicals known to the state of California to cause cancer or reproductive toxicity. If this product is reformulated or further processed, further evaluation should be done based upon such reformulation or processing, as well as upon its final composition and use.

#### **SECTION 16: OTHER INFORMATION**

#### **US NFPA Codes**

Health	Fire	Reactivity	Special
1	1	0	N/E

# **HMIS Codes**

Health	Fire	Reactivity
1	1	0

Date: 20 August 2013 Revision Date: None Revision Indicators: None

#### DISCLAIMER OF LIABILITY

The information in this MSDS was obtained from sources, which we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT.

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.